


SMV100 3-36 SAH



Standard equipment:

- 0.144.0108 HEPA (H14) + PTFE cartridge filter (3x)
- 0.144.0008 Quick release adaptor Ø60-50 (1x)
- There isn't any hose or tool provided within the unit.

Optional minimum set to run the unit:

- 6.205.0049 3m complete EVA Ø50 hose set (1x)

Optional:

Longopack set

- 0.144.0110 Hopper for spool bag collection
- 0.144.0111 Tray for spool bag collection
- 0.144.0112 Longopack 22m bag spools (box of 4)

Filter

- 0.144.0109 ULPA (H13) D.O.P. cartridge filter

Equipped with:

- 3 silenced two stage by-pass cooling motors
- Power coated steel structure and containers
- Self-cleaning filter system for continuous operations
- 3 HEPA + PTFE cartridge conductive filters
- Metal side inlet channel and AISI 304 stainless steel filter protection
- Wheeled container with inbuilt quick release handle, drain plug and full load level
- Trolley with front pivoting non-marking wheels (with breake) & large inbuilt accessories basket
- Removable motors unit header through metal hooks

	SMV100 3-36 SAH
code	0.044.0301
abs. power W	3600
n°/type motor	3 x two stages universal
max vacuum (actual)	24 kPa (24kPa)
max Airflow	510 m³/h - 142 l/s
container capacity	100 l
noise level	78 dB(A)
voltage	230 V~50 Hz (1Ph)
inlet Ø - type (s=straight; t=tangential)	60 mm - t
filtering capacity/surface	1 µm - 99,995% (H Class)/ 9000 cm²
cable lenght	10 m
dimensions/weight	60x80x147 cm/59 kg - 130 lb