

**DMX80
DTX80**



Standard equipment:

- Flexible hose ø 40 - 3 m
code 5.209.0159



- Flat lance ø 40
code 3.754.0048



- Cloth filter
code 5.509.0039



Optional:

- Washable filter
5.212.0021



- Kit 6.205.0115

- Steel curve + pipe
Ø 40



- Round brush Ø 40



- Accessories holder Ø 40



- Floor Brush



- Wet tool



- Carpet tool



Equipped with:

- IP 65 silenced turbine motor. • Liquid float valve. Washable filter. • S. S. tank. • Manual filter shaker. • Professional closing hooks. • Static electric shock inhibitor. • Non-overturning steel structure. • Drain hose system. • Epoxy varnishing. • Steering wheels with brake. • Air intake safety valves for turbine motor protection.

	DMX80 1-22 S	DTX80 1-30 S
code	0.045.0031	0.045.0032
abs. power W	2200	3000
n° / type motor	1x induction	1x induction
column depression	32 kPa (3200 mmH2O)	32 kPa (3200 mmH2O)
suction air	97 l/s	97 l/s
tank volume/dust capacity/liquid capacity	80/36/49 lt	80/36/49 lt
noise level	74 dB(A)	74 dB(A)
voltage	230 V~50 Hz (1Ph)	400 V~50 Hz (3Ph)
filtering surface	4300 cm ²	4300 cm ²
filtering capacity	5 µm	5 µm
cable length	10 m	10 m
dimensions / weight	50x50x140cm/80Kg -176 lbs	50x50x140cm/85Kg -187 lbs