

LITE 1510 XP
LITE PRO 1510 LP

NEW



LITE 1510 XP model

LITE PRO 1510 LP model

Equipped with:

- Three steel pistons, brass axial pump head with built-in by-pass valve (LITE 1510 XP)
- Three full ceramic pistons, brass linear pump head with by-pass valve (LITE PRO 1510 LP)
- Easy to transport thanks to a practical top grip and anti-vibration supports
- Induction 2-pole motor (2800 rpm) on LITE 1510 XP model • 4-pole motor (1400 rpm) on LITE PRO 1510 LP model • Glycerine pressure gauge. • EASY START device
- Total Stop system • Rotary switch • Motor thermal protection

Standard equipment:

- 0.966.0093 Gun G1/4" M (mod. LITE 1510 XP)
- 0.966.0092 Gun G3/8" M (mod. LITE PRO 1510 LP)
- 0.966.0096 Lance M22 high/low pressure (mod. LITE 1510 XP)
- 0.966.0094 Lance M22 high/low pressure (mod. LITE PRO 1510 LP)
- 0.966.0097 Nozzle (mod. LITE 1510 XP)
- 0.966.0037 S.S. nozzle (mod. LITE PRO 1510 LP)

- 0.966.0098 H.p. hose 10 m (mod. LITE 1510 XP)
- 0.966.0099 H.p. hose 10 m (mod. LITE PRO 1510 LP)

- Power cable 5 m

Optional:

- 0.966.0100 ROTOX lance (mod. LITE 1510 XP)
- 0.966.0087 ROTOX lance (mod. LITE 1510 PRO LP)

| | LITE 1510 XP | LITE PRO 1510 LP |
|------------------------------|---------------------------|---------------------------|
| code | 0.066.0031 | 0.066.0032 |
| operat. pressure/max | 135/150 bar-1958/2175 psi | 135/150 bar-1958/2175 psi |
| delivery rate | 600 l/h-2.64 GPM | 600 l/h-2.64 GPM |
| abs. power/voltage | 2900W - 230V~50Hz 1 ph | 2900W - 230V~50Hz 1 ph |
| motor/pump type/RPM | GXR/2800 RPM | LW-K250/1400 RPM |
| max. water inlet temperature | 60 °C | 60 °C |
| dimension/weight | 26x47h37cm/25 Kg - 55 lbs | 26x47h37cm/35 Kg - 77 lbs |