



SCRUBBER DRYERS - WALK BEHIND

# CT51

**MAX PRODUCTIVITY**

Up to  
**3150** m<sup>2</sup>/h

**BATTERIES  
RUNNING TIME**

**3,5** h

**WATER TANK  
RUNNING TIME**

Up to **60'**  
working session



MEMORY CARD

**TELEMATICS GPS** (opt)  
GEOLOCATION OF  
ALL YOUR MACHINES

**ANC**  
ADVANCE NOISE CONTROL  
**54 dB** IN ECO SELECT MODE



**ORBITAL VERSION**



**ONE BRUSH VERSION**



**ROLLER VERSION**



BATTERIES AND BATTERY CHARGER NOT INCLUDED

**MOST FREQUENTLY USE**

RETAIL

HORECA

CLEANING CONTRACTORS

MUNICIPALITIES

**INNOVATIONS**

INTER-CHANGEABLE BRUSH HEAD	<b>600 RPM</b> INTERCHANGEABLE BRUSH HEAD	ORBITAL BRUSH	ANCTM <sup>™</sup> ADVANCED NOISE CONTROL	DBL <sup>™</sup> DOUBLE BATTERY LIFE
MEMORY CARD	TELEMATICS GPS	SLS <sup>™</sup> SELF LEVELING SYSTEM	ECO SELECT	SERVICE MENU
				BACTERIA CONTROL


**SPECS**



ADJUSTABLE HANDLE FOR A COMFORTABLE AND EASY USE.



FULL MACHINE CONTROL THANKS TO AN INTUITIVE CENTRAL KNOB.



EASY ACCESS NO TOOLS

## TECHNICAL DATA

### WITHOUT ELECTRIC TRACTION

### WITH ELECTRIC TRACTION

Code		CT51 B50 LPTB02976	CT51 B55 LPTB01822	CT51 BT55 LPTB01823	CT51 BT60 LPTB01826	CT51 BT70 LPTB01824
<b>PERFORMANCE</b>						
Max theoretical productivity	m <sup>2</sup> /h	1850	1925	2475	2700	3150
Cleaning path	mm	500	550	550	600	700
Water tank capacity (solution recovery)	l	50/53	50/53	50/53	50/53	50/53
Max running time	min	210	210	210	210	210
Voltage	V-Ah	24	24	24	24	24
Installed power	W	800	800	1000	1400	1400
Brush pressure	kg	18	18	18	23	23
Squeegee width	mm	815	815	815	815	940
Max speed	km/h	3,5	3,5	4,5	4,5	4,5
Weight (Without Batteries)	kg	81,1	81,4	89,1	97,1	94,6
Dimension (LxWxH)	mm	1328 x 563 x 1033	1328 x 563 x 1033	1329 x 563 x 1033	1279 x 653 x 1033	1279 x 735 x 1033

## STANDARD EQUIPMENT

	CT51 B50	CT51 B55	CT51 BT55	CT51 BT60	CT51 BT70
<b>BRUSHES</b>					
PPL SOFT	SPPV01332	SPPV01352	SPPV01352	2XSPPV01473	2xSPPV01472
<b>SQUEEGEE BLADES</b>					
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08039 - 880mm	MPVR08040 - 1020mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08035 - 900mm	MPVR08036 - 1020mm

## CABLE

Code		CT51 C50 230V LPTE00669	CT51 C55 230V LPTE00646
<b>PERFORMANCE</b>			
Max theoretical productivity	m <sup>2</sup> /h	1850	1925
Cleaning path	mm	500	550
Water tank capacity (solution recovery)	l	50/53	50/53
Max running time	min	Unlimitess	Unlimitess
Voltage	V-Ah	230	230
Installed power	W	1100	1100
Brush pressure	kg	18	18
Squeegee width	mm	815	815
Max speed	km/h	3,5	3,5
Weight (Without Batteries)	kg	102	102,1
Dimension (LxWxH)	mm	1329 x 563 x 1033	1329 x 563 x 1033

## STANDARD EQUIPMENT

	CT51 C50 230V	CT51 C55 230V
<b>BRUSHES</b>		
PPL SOFT	SPPV01332	SPPV01352
<b>SQUEEGEE BLADES</b>		
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08035 - 900mm

## TECHNICAL DATA

### WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

### ROLLER - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

Code		CT51 XP60 LPTB01828	CT51 XP70 LPTB01825	CT51 XP55R LPTB01834
<b>PERFORMANCE</b>				
Max theoretical productivity	m <sup>2</sup> /h	2700	3150	2475
Cleaning path	mm	600	700	550
Water tank capacity (solution recovery)	l	50/53	50/53	50/53
Max running time	min	210	210	210
Voltage	V-Ah	24	24	24
Installed power	W	1450	1450	2350
Brush pressure	kg	31	31	18
Squeegee width	mm	815	940	815
Max speed	km/h	4,5	4,5	4,5
Weight (Without Batteries)	kg	97,1	94,6	107
Dimension (LxWxH)	mm	1279 x 653 x 1033	1279 x 735 x 1033	1329 x 563 x 1033

## STANDARD EQUIPMENT

	CT51 XP60	CT51 XP70	CT51 XP55R
<b>BRUSHES</b>			
PPL SOFT	2xSPPV01473	2XSPPV01472	-
CYLINDRICAL BRUSH - PPL SOFT Ø 0,3 mm	-	-	SPPV01163
<b>SQUEEGEE BLADES</b>			
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08040 - 1020mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08036 - 1020mm	MPVR06288 - 715mm

### 600 RPM - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

### ORBITAL - WITH ELECTRIC TRACTION AND ELECTRONIC BRUSH PRESSURE CONTROL

Code		CT51 XP55 600 RPM LPTB01832	CT51 XP70 600 RPM LPTB01833	CT51 XP20" ORBITAL LPTB01670
<b>PERFORMANCE</b>				
Max theoretical productivity	m <sup>2</sup> /h	2475	3150	2794
Cleaning path	mm	550	700	500
Water tank capacity (solution recovery)	l	50/53	50/53	50/53
Max running time	min	210	210	210
Voltage	V-Ah	24	24	24
Installed power	W	1080	1480	1080
Brush pressure	kg	26	31	45,7
Motor Brush RPM	rpm	600	600	2200
Squeegee width	mm	815	940	815
Max speed	km/h	4,5	4,5	4,2
Weight (Without Batteries)	kg	89,1	94,6	107,2
Dimension (LxWxH)	mm	1329 x 563 x 1033	1279 x 735 x 1033	1225 x 512 x 1033










## STANDARD EQUIPMENT

	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP20" ORBITAL
<b>PAD HOLDER</b>			
MICROFIBER PAD HOLDER	SPPV01978	2x SPPV01983	-
DIAMOND PAD HOLDER	SPPV01348	2x SPPV01228	-
<b>SQUEEGEE BLADES</b>			
LATEX FRONT BLADE	MPVR08039 - 880mm	MPVR08040 - 1020mm	MPVR08039 - 880mm
LATEX REAR BLADE	MPVR08035 - 900mm	MPVR08036 - 1020mm	MPVR08035 - 900mm









**CONSUMABLES (Codes available on price list)**

	CONSUMABLES	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT60	CT51 BT70	CT51 XP60	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP50 ORBITAL
	Brushes	available on price list	•	•	•	•	•	•	•	•	•	•	•		
	Roller Brushes	available on price list												•	
	Pad holder	available on price list	•	•	•	•	•	•	•	•	•	•	•		
	Pads / Super pads	available on price list	•	•	•	•	•	•	•	•	•	•	•		
	Orbital pads	available on price list													•
	Microfiber pads	available on price list										•	•		
	Diamond pads	available on price list										•	•		
	Squeegee blades	available on price list	•	•	•	•	•	•	•	•	•	•	•	•	•

**OPTIONAL ACCESSORIES**

	BRUSH HEAD	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT60	CT51 BT70	CT51 XP60	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP20" ORBITAL	
	C50 C55 B50 B55		NOT INTERCHANGEABLE BRUSH HEAD													
	BT55	KTRI04851					•	•	•	•	•	•	•	•	•	
	BT60	KTRI04852					•	•	•	•	•	•	•	•	•	
	BT70	KTRI04853					•	•	•	•	•	•	•	•	•	
	XP55 600 RPM	KTRI04855								•	•	•	•	•	•	
	XP70 600 RPM	KTRI04856								•	•	•	•	•	•	
	XP55 ROLLER	KTRI04854								•	•	•	•	•	•	
	XP20" ORBITAL	KTRI05787								•	•	•	•	•	•	
	Kit Telematic Basic	KTRI06165			•	•										
		KTRI06163					•	•	•	•	•	•	•	•	•	•
	Kit Telematic Full	KTRI06164			•	•										
		KTRI06024					•	•	•	•	•	•	•	•	•	•

## OPTIONAL ACCESSORIES

	OPTIONAL	CODE	CT51 C50	CT51 C55	CT51 B50	CT51 B55	CT51 BT55	CT51 BT60	CT51 BT70	CT51 XP60	CT51 XP70	CT51 XP55 600 RPM	CT51 XP70 600 RPM	CT51 XP55 R	CT51XP50 ORBITAL
	Chem dose kit	KTRI04846			•	•	•	•	•	•	•	•	•	•	•
	Splash guard 50/55 cm	KTRI04847		•		•	•					•			
	Splash guard 60 cm	KTRI05094						•		•					
	Splash guard 70 cm	KTRI05095							•		•		•		
	Tools bar	KTRI04848	•	•	•	•	•	•	•	•	•	•	•	•	•
	Auto-Refill System	KTRI04849	•	•	•	•	•	•	•	•	•	•	•	•	•
	External suction kit	KTRI02257	•	•	•	•	•	•	•	•	•	•	•	•	•
	BIOSAN RAPIDE WT (30 pcs / 30 days)	PRCH00578	•	•	•	•	•	•	•	•	•	•	•	•	•

## BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTICS	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x285	210 min	DBL on board high freq. 24V 15 Ah- KTRI04845 DBL stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x174x283	210 min	DBL on board high freq. 24V 15 Ah KTRI04845 DBL stand alone high frequency BLS010 BACA00133
EXIDE gel battery BAAC00132	2	12V 76 Ah (C5)	330x171x236	150 min	DBL on board high freq. 24V 15 Ah KTRI04845 DBL stand alone high frequency BLS010 BACA00133
Acid tubular plate BAAC00136	2	12V 85 Ah (C5)	308x175x225	150 min	DBL on board high freq. 24V 15 Ah KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone Low frequency 24V 12 Ah BACA0060
Dry charge flate plate BAAC00009	2	12V 105 Ah (C5)	261x171x210	210 min	DBL on board high freq. 24V 15 Ah KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone Low frequency 24V 12 Ah BACA0060
Acid tubular plate BAAC00070	2	12V 118 Ah (C5)	345x170x285	210 min	DBL on board high freq. 24V 15 Ah KTRI04845 DBL stand alone high frequency BLS010 BACA00133 Stand alone Low frequency 24V 12 Ah BACA0060

RECOMMENDED BATTERIES AND BATTERY CHARGER