

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 12.12.2022 Revision date: 04.06.2014 Supersedes version of: 05.12.2017 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : COYOTE Silkal 93
Product code : CY-1031200008, CY-1031200009, CY-1031200010, CY-1031206000

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Lubricating and impregnating silicone oil in aerosol packaging

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AutoMax Group s.r.o.
K Hájům 1233/2
155 00 Praha 5
T +420 272 700 530 - F +420 272 700 531
info.cz@automax-group.com - www.automax-group.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Cardiff Centre) University Hospital Llandough	Penlan Road CF64 2XX	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Edinburgh Centre) Royal Infirmary of Edinburgh	Little France Crescent EH16 4SA	0344 892 0111	Only for healthcare professionals
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

Contains

: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (total aromatic hydrocarbons <0.01%)

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing aerosols.
P264 - Wash hands thoroughly after handling with water/soap.
P273 - Avoid release to the environment.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 - Dispose of contents and container to as hazardous waste.

2.3. Other hazards

Other hazards which do not result in classification : The mixture doesn't meet the criteria for classification as PBT or vPvB substances and mixtures.

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isobutane	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	< 65	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	< 10	Flam. Gas 1, H220 Press. Gas (Comp.), H280
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (total aromatic hydrocarbons <0.01%)	EC-No.: 921-024-6 REACH-no: 01-2119475514-35	< 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Butane	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	< 5	Flam. Gas 1, H220 Press. Gas (Comp.), H280

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep them warm and calm.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. If irritation persists, consult a doctor.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Consult an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Do not induce vomiting. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: In case of fire may release toxic fumes/ vapours.
Explosion hazard	: Contains gas under pressure; may explode if heated.

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Firefighting instructions : During the fire of the product, keep the safe distance, use suitable breathing protection (isolation device), or self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Ventilate spillage area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Concerning personal protective equipment to use, see section 8.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow the mixture to enter into sewer, water system (underground water, surface water) or soil.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not breathe vapour/aerosol. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not expose to temperatures exceeding 50 °C/ 122 °F. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, cool, and well-ventilated areas in the original package. Keep the package closed tightly. Do not store together with drugs, foodstuffs, drinks, and forage. . Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Isobutane (75-28-5)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
OEL STEL	1000 mg/m ³
OEL STEL [ppm]	1000 ppm

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutane (75-28-5)	
Regulatory reference	Chemical Agents Code of Practice 2021
Propane (74-98-6)	
Ireland - Occupational Exposure Limits	
Local name	Propane
OEL TWA [2]	1000 ppm
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2021
Butane (106-97-8)	
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Butane
OEL TWA [2]	1000 ppm
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA) [1]	1450 mg/m ³
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m ³
WEL STEL (OEL STEL) [ppm]	750 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage, only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

COYOTE Silkal 93	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m ³
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day

8.1.5. Control banding

No additional information available

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Not necessary, if the product is used in accordance with section 1.2.

8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

No additional information available

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: yellowish.
Appearance	: Aerosol.
Odour	: organic solvents.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosion limits	: Not available
Lower explosion limit	: 1,4 vol %
Upper explosion limit	: 11,2 vol %
Flash point	: -80 °C (isobutane-propane-butane)
Auto-ignition temperature	: 365 °C (isobutane-propane-butane)
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 400 kPa (20 °C)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 630 – 660
Relative vapour density at 20°C	: 1,79 – 1,94
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0,8

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known under normal conditions of use.

10.4. Conditions to avoid

Do not expose to temperatures exceeding 50 °C/ 122 °F.

10.5. Incompatible materials

Oxidizing agent. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Nitrogen oxides. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (total aromatic hydrocarbons <0.01%)

LD50 oral rat	> 5840 mg/kg
LD50 dermal rabbit	2800 – 3100 mg/kg
LC50 Inhalation - Rat	25,2 mg/l/4h

Butane (106-97-8)

LC50 Inhalation - Rat	1442 mg/l
-----------------------	-----------

Skin corrosion/irritation : Based on available data, the classification criteria are not met.
Serious eye damage/irritation : Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.
Germ cell mutagenicity : Based on available data, the classification criteria are not met.
Carcinogenicity : Based on available data, the classification criteria are not met.
Reproductive toxicity : Based on available data, the classification criteria are not met.
STOT-single exposure : Based on available data, the classification criteria are not met.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (total aromatic hydrocarbons <0.01%)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Based on available data, the classification criteria are not met.
Aspiration hazard : Based on available data, the classification criteria are not met.

Propane (74-98-6)

Vaporizer	Spray
-----------	-------

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane (total aromatic hydrocarbons <0.01%)

LC50 - Fish [1]	11,4 mg/l
EC50 - Crustacea [1]	3 mg/l
EC50 72h - Algae [1]	10 – 30 mg/l
NOEC chronic fish	2,045 (21 days)
NOEC chronic crustacea	0,17 mg/l (21 days)

Butane (106-97-8)

LC50 - Fish [1]	24,11 (24,11 – 147,54) mg/l
EC50 - Crustacea [1]	14,22 (14,22 – 69,43) mg/l
EC50 72h - Algae [1]	7,71 (7,71 – 19,37) mg/l

12.2. Persistence and degradability

COYOTE Silkal 93

Persistence and degradability : Hardly biodegradable.

Butane (106-97-8)

Persistence and degradability : Readily biodegradable.

12.3. Bioaccumulative potential

Butane (106-97-8)

Partition coefficient n-octanol/water (Log Pow) : 1,09 – 2,8 (20 °C, pH 7)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations






13.1. Waste treatment methods

Waste treatment methods

: Collect all waste in suitable and labelled containers and dispose according to local legislation. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Container under pressure. Do not drill or burn even after use.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description (ADR)				
UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Air transport

No data available

Inland waterway transport

Classification code (ADN) : 5F

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 0,8

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

Not available.

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
1-16	SDS EU format according to COMMISSION REGULATION (EU) 2020/878	Modified	12.12.2022

COYOTE Silkal 93

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information

: Prior to using this product, read the Safety Recommendations included herein and in the box of the product.
This product has to be handled carefully and only used by authorised workers who hold the official accreditation when so required by law.
The product must be stored, handled and used in accordance with the procedures of good industrial hygiene practices and pursuant to the applicable legal regulations.

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	Expert judgment
Skin Irrit. 2	H315	Expert judgment
STOT SE 3	H336	Expert judgment
Aquatic Chronic 3	H412	Expert judgment

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.