





www.mafra.com

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: STČ
- **UFI**: NDK0-80AA-Q00J-7SNK
- -1.2 Relevant identified uses of the substance or mixture and uses advised against
- Life cycle stages PW Widespread use by professional workers
- -Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC1 Adhesives, sealants
- Application of the substance / the mixture Sealant
- Uses advised against

The mixture is not raccomended for industrial, professional and consumer applications not specified as relevant identified uses

- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MA-FRA S.p.A. a Socio Unico Via Aquileia, 44/46 20021 Baranzate (MI) ITALIA Tel.+39 023569981 www.mafra.com mafra@mafra.it

- Informing department:

E-mail: lab@mafra.it

info@mafra.it

- 1.4 Emergency telephone number: In case of accident call the emergency number 112

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

- Hazard pictograms

(Contd. of page 1)







GHS02 GHS07 GH

- Signal word Danger
- Hazard-determining components of labelling:

di-n-butyl ether

- Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulation

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- **PBT**: Not applicable. - **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances

Dangerous components:		·
CAS: 142-96-1 EINECS: 205-575-3	di-n-butyl ether ♠ Flam. Liq. 3, H226; ♠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3,	25-35%
Envecs. 203-373-3	H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: $C \ge 10\%$	
CAS: 68037-85-4	Methoxy siloxanes	25-35%
EC number: 614-229-4	♦ Flam. Liq. 3, H226	
CAS: 8052-41-3	Stoddard solvent	5-10%
EINECS: 232-489-3	🊸 Flam. Liq. 3, H226; 🗞 STOT RE 1, H372; Asp. Tox. 1, H304	
CAS: 1185-55-3	trimethoxy(methyl)silane	3-5%
EINECS: 214-685-0	♦ Flam. Liq. 2, H225	
Reg.nr.: 01-2119517436-40		

- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

(Contd. of page 2)

Instantly remove any clothing soiled by the product.

- After inhalation

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult doctor in case of symptoms.

- After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- After swallowing

In case of persistent symptoms consult doctor.

Do not induce vomiting; instantly call for medical help.

-4.2 Most important symptoms and effects, both acute and delayed

Sickness

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation

Medical supervision for at least 48 hours

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, sand, extinguishing powder. Do not use water.

Use fire fighting measures that suit the environment.

- For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

- 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Bring persons out of danger.

Keep away from ignition sources

- 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

-6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

Use only in well ventilated areas.

Store in cool, dry place in tightly closed containers.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers:

Store in cool location.

Store only in the original container.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

- Class according to regulation on inflammable liquids: A I
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- DNELs			
1185-55-3	1185-55-3 trimethoxy(methyl)silane		
Inhalative	Systemic long-term effects	260 mg/m³ (Industrial Workers)	
		50 mg/m³ (Consumers)	
5593-70-4	5593-70-4 tetra-n-butoxytitanium		
Oral	Systemic Long-term Effects	3.75 mg/Kg bw/day (Consumers)	
Dermal	Systemic long-term effects	37.5 mg/Kg bw/day (Consumers)	
Inhalative	Systemic long-term effects	127 mg/m³ (Industrial Workers)	
		152 mg/m³ (Consumers)	

- PNECs

5593-70-4 tetra-n-butoxytitanium

) ')
)
)
)

- Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Version number 2 (replaces version 1) Printing date 10.01.2022 Revision: 10.01.2022

Trade name: STC

- Breathing equipment:

(Contd. of page 4)





Breathing protection recommended.

Filter A/P2.

- Hand protection



Protective gloves. (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Recommended thickness of the material: ≥ 0.5 mm

Nitrile rubber, NBR

PVC gloves

- Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 240 minutes (Permeation according to EN 16523-1:2015: Level 5).

Eye/face protection



Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour: Colourless - Odour: Solvent-like - Odour threshold: Not determined. - Melting point/freezing point: Not determined 100 °C

- Boiling point or initial boiling point and boiling range

- Flammability Not applicable.

- Lower and upper explosion limit

0.9 Vol % -Lower: 8.5 Vol % - Upper: 16 °C - Flash point:

- Self-inflammability: Product is not selfigniting.

- Decomposition temperature: Not determined. -*pH* Not applicable.

- Viscosity:

- Kinematic viscosity Not determined. - dynamic: Not determined.

- Solubility

Not miscible or difficult to mix - Water:

- Partition coefficient n-octanol/water (log value) Not determined. - Vapour pressure at 20 °C: 400 hPa

- Density and/or relative density

- Density at 20 °C $0.93 \, g/cm^3$ - Relative density Not determined. - Vapour density Not determined.

(Contd. on page 6)

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

	(Contd. of page 5
- 9.2 Other information	
- Appearance:	
- Form:	Fluid
-Important information on protection of hea	alth and
environment, and on safety.	
- Ignition temperature:	175 °C
- Explosive properties:	Product is not explosive. However, formation of explosive air/ steam mixtures is possible.
- Change in condition	-
- Evaporation rate	Not determined.
- Information with regard to physical hazard class	ses
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	
Highly flammable liquid and vapour.	
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
-Substances and mixtures, which emit flammable	O .
contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Flammable
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Flammable
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC5	- LD/LC50 values that are relevant for classification:		
142-96-	142-96-1 di-n-butyl ether		
Oral	<i>LD50</i>	7,400 mg/Kg (Rat)	
Dermal	<i>LD50</i>	10,000 mg/Kg (Rabbit)	
	1185-55-3 trimethoxy(methyl)silane		
Oral	LD50	11,685 mg/Kg (Rat)	
Dermal	LD50	>9,500 mg/Kg (Rabbit)	
		(Contd. on page 7)	

-GR

Version number 2 (replaces version 1) Printing date 10.01.2022 Revision: 10.01.2022

Trade name: STC

5593-70-4 tetra-n-butoxytitanium

(Contd. of page 6)

|LD50| >2,000 mg/Kg (Rat) Oral

- Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure.

- Aspiration hazard Based on available data, the classification criteria are not met.
- -11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

-12.1 Toxicity

- Aquatic toxicity:

1185-55-3 trimethoxy(methyl)silane

LC50 (96h) > 110 mg/L (Fish)

EC50 (48h) > 122 mg/L (Daphnia)

EC50 (72h) > 3.6 mg/L (Algae)

5593-70-4 tetra-n-butoxytitanium

LC50 (96h) 1,740 mg/L (Fish)

EC50 (48h) 1,983 mg/L (Daphnia)

- -12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT**: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

- Uncleaned packagings:

(Contd. of page 7)

- Recommendation: Disposal must be made according to official regulations.

	on
- 14.1 UN number or ID number	
- ADR, IMDG, IATA	UN1993
- 14.2 UN proper shipping name	
-ADR	FLAMMABLE LIQUID, N.O.S. (vapour pressure at 50°C not mor
Heng vimi	than 110 kPa) (DIBUTYL ETHERS)
- IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (DIBUTYL ETHERS, Methox siloxanes)
- 14.3 Transport hazard class(es)	·
- ADR, IMDG, IATA	
- Class	3 Flammable liquids.
- Label	3
- 14.4 Packing group	
- ADR, IMDG, IATA	II
- 14.5 Environmental hazards:	Not applicable.
- 14.6 Special precautions for user	Warning: Flammable liquids.
- Kemler Number:	33
- EMS Number:	F-E, <u>S-E</u> B
- Stowage Category	
- 14.7 Maritime transport in bulk according	
instruments	Not applicable.
- Transport/Additional information: - ADR	
- Limited quantities (LQ)	IL
- Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
T	Maximum net quantity per outer packaging: 500 ml
- Transport category	2
- Tunnel restriction code - IMDG	D/E
- IMDG - Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

- -15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

(Contd. on page 9)

(Contd. of page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.01.2022 Version number 2 (replaces version 1) Revision: 10.01.2022

Trade name: STC

- National regulations

- Classification according to VbF: A I - Technical instructions (air):

Class	Share in %
NK	30.0

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing data specification sheet: Ma-Fra Laboratories

- Contact: lab@mafra.it

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- * Data compared to the previous version altered.





www.mafra.com

Page 1/9

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: HPC PRO
- UFI: CA96-DOVG-Y00H-JCNJ
- -1.2 Relevant identified uses of the substance or mixture and uses advised against
- Life cycle stages PW Widespread use by professional workers
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Recommended use Chemical sealants
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MA-FRA S.p.A. a Socio Unico

Via Aquileia, 44/46

20021 Baranzate (MI) ITALIA

Tel.+39 023569981

www.mafra.com

mafra@mafra.it

- Informing department: info@mafra.it
- -1.4 Emergency telephone number: In case of accident call the emergency number 112

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

- Hazard pictograms









GHS02

GHS05 GHS0

- Signal word Danger
- Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light

Organic polysilazane compound

- Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H304 May be fatal if swallowed and enters airways.

- Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international

regulation

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- **Description:** Mixture of substances

- Dangerous components:			
CAS: 64742-46-7 EINECS: 265-148-2	Distillates (petroleum), hydtrotreated middle	♦ Asp. Tox. 1, H304	30-50%
CAS: 475645-84-2	Organic polysilazane compound	♦ Skin Corr. 1B, H314	30-50%
- Regulation (EC) No 648/2004			

liphatic hydrocarbons	≥30%

- Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.2 Most important symptoms and effects, both acute and delayed Unconsciousness

- General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation

Supply fresh air; consult doctor in case of symptoms.

Call a doctor immediately.

(Contd. on page 3)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 2)

- After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

Use eye protection.

- After swallowing Call a doctor immediately.
- 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation

Medical supervision for at least 48 hours

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

Can be released in case of fire

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- Protective equipment:

Do not inhale explosion gases or combustion gases.

Protection means for respiratory tract

- Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Bring persons out of danger.

Keep away from ignition sources

Protective gloves. (EN 374)

- For non-emergency personnel

Ensure adequate ventilation

Keep away from ignition sources

Wear protective clothing.

- For emergency responders Nitrile rubber, NBR
- 6.2 Environmental precautions:

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

- GE

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 3)

SECTION 7: Handling and storage

-7.1 Precautions for safe handling

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not eat, drink or smoke while working.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Class according to regulation on inflammable liquids: A II
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- Breathing equipment: Not required.
- Hand protection



Protective gloves. (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection



Tightly sealed safety glasses.

(Contd. on page 5)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 4)

- Environmental exposure controls

Disposal must be made according to official regulations.

Dispose of packaging according to regulations on the disposal of packagings.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Physical state
- Colour:
- Odour:
- Odour threshold:
- Melting point/freezing point:
- Boiling point or initial boiling point and boiling range
- Flammability

Flammable.

- Tummaviniy

- Lower and upper explosion limit

Lower: 0.7 Vol % (64742-47-8 Distillates (petroleum), hydrotreated light)
 - Upper: 6.5 Vol % (64742-47-8 Distillates (petroleum), hydrotreated light)

- Flash point: 49 °C

- Decomposition temperature: Not determined.

-pH Mixture is non-soluble (in water).

- Viscosity:

- Kinematic viscosity
- dynamic at 20 °C:

Not determined.
20-50 mPas

- Solubility

- Water: Not miscible or difficult to mix

- Partition coefficient n-octanol/water (log value)
 - Vapour pressure:
 Not determined.
 Not determined.

- Density and/or relative density

- Density at 20 °C 0.75 g/cm³
- Relative density Not determined.
- Vapour density Not determined.

- 9.2 Other information

- Appearance:

- Form: Fluid
- Important information on protection of health and

environment, and on safety.

- Self-inflammability: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/

steam mixtures is possible.

- Change in condition

- Evaporation rate Not determined.

- Information with regard to physical hazard classes

- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void

- Flammable liquids Flammable liquid and vapour.

- Flammable solids Void
- Self-reactive substances and mixtures Void

(Contd. on page 6)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

		(Contd. of page 5)
- Pyrophoric liquids	Void	
- Pyrophoric solids	Void	
- Self-heating substances and mixtures	Void	
- Substances and mixtures, which emit flammable	gases in	
contact with water	Void	
- Oxidising liquids	Void	
- Oxidising solids	Void	
- Organic peroxides	Void	
- Corrosive to metals	Void	
- Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Flammable
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Flammable
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values that are relevant for classification:		
64742-46-7 Distillates (petroleum), hydtrotreated middle		
Dermal LD	0 3,160 mg/Kg (Rabbit)	

63148-62-9 Poly (dimethylsiloxane)

Oral	LD50	>15,400 mg/Kg (Rat)
Dermal	<i>LD50</i>	>15,400 mg/Kg (Rat) >2,000 mg/Kg (Rabbit)
		>2,000 mg/Kg (Rat)

- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation No sensitizing effect known.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

GE

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 6)

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

64742-46-7 Distillates (petroleum), hydtrotreated middle

LC50 (4 h) 5,266 mg/L (Rat)

63148-62-9 Poly (dimethylsiloxane)

EC50 (48h) > 200 mg/L (Daphnia)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT**: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Additional ecological information:
- General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation:

Disposal must be made according to official regulations.

Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA

UN2924

- 14.2 UN proper shipping name
- ADR, IMDG, IATA

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Organic polysilazane compound, Distillates (petroleum), hydrotreated light)

- 14.3 Transport hazard class(es)
- ADR





- Class 3 Flammable liquids.

(Contd. on page 8)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 7) 3+8 - Label - IMDG - Class 3 Flammable liquids. - Label - IATA 3 Flammable liquids. - Class - Label 3 (8) - 14.4 Packing group III- ADR, IMDG, IATA - 14.5 Environmental hazards: Not applicable. Warning: Flammable liquids. - 14.6 Special precautions for user - Kemler Number: 38 F-E,S-C- EMS Number: - Stowage Category - Stowage Code SW2 Clear of living quarters. - 14.7 Maritime transport in bulk according to IMO instruments Not applicable. - Transport/Additional information: - ADR - Limited quantities (LQ) 5L- Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - Transport category D/E- Tunnel restriction code - IMDG 5L- Limited quantities (LQ)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

- Poisons Act
- Regulated explosives precursors

- Excepted quantities (EQ)

None of the ingredients is listed.

- Regulated poisons

None of the ingredients is listed.

(Contd. on page 9)

Printing date 12.06.2024 Version number 1 Revision: 12.06.2024

Trade name: HPC PRO

(Contd. of page 8)

- Reportable explosives precursors

None of the ingredients is listed.

- Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations
- Classification according to VbF: A II
- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- -15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- Relevant phrases

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

- Department issuing data specification sheet: Ma-Fra Laboratories
- Contact: lab@mafra.it

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

GB